

Lite-Ex[®] PL

AN ULTRA LIGHT AND BRIGHT TORCH, DESIGNED FOR EVERYDAY USE IN HAZARDOUS AREAS.

Despite its compact dimensions, the Lite-Ex[®] PL 10 is equipped with all of the features of its larger sibling.

It comes with the tried and tested, wear-resistant ring switch and a high performance LED. Its sophisticated lens ensures even and consistent illumination.



Lite-Ex[®] PL 10

LED FLASHLIGHT FOR ZONE 0 / 20

TECHNICAL DATA	
Ambient temperature	-20 °C ... +50 °C
Storage temperature	-30 °C ... +60 °C (without batteries)
Power supply	3 x LR03 / AAA (type-tested)
Bulb	High performance LED
Luminosity	3,000 lux (at a distance of 1 m)
Luminous flux	64 lumens
Operating time	approx. 55 hrs
Dimensions	147 x 36 x 36 mm
Weight	approx. 120 g (with batteries)
IP protection class	IP65 / IP67
ESD protection	Anti-static housing
CE-designation	CE 0102

SCOPE OF DELIVERY

- Lite-Ex[®] PL 10
- Batteries
- Belt clip
- Wrist strap
- User manual
- Ex-certificate
- EC Declaration of Conformity

















10 HIGH PERFORMANCE LED



FEATURES

- Zone 0/20
- High performance LED
- Luminosity: 3,000 lux (at a distance of 1 m)
- Extremely light and compact.
Weight: only 120 g including batteries
- Operating time: approx. 55 hours
- Ring switch, easy to use
- Scratch-resistant thanks to the coated protective disc
- Rugged polyamide housing
- Diaphragm valve for pressure compensation
- Removable belt clip

ACCESSORIES

	ARTICLE NO.	PRODUCT DESCRIPTION
	A0002044 	Belt clip
	A0002045 	Hand strap
	A0002046 	Ring switch
	A0002047 	Sealing kit
	A0002048 	Replacement lens
	A0002049 	Battery housing
	A0002050 	Lamp head (only plastic part)
	A0002051 	Leather holster

EX DATA

ATEX



⊕ II 1 G Ex ia op is IIC T4 Ga
⊕ II 1 D Ex ia IIIC T130°C Da

IECEX



Ex ia op is IIC T4 Ga
Ex ia IIIC T130°C Da IP65

EMEA

Germany (Headquarters) ¹

ecom instruments GmbH
Industriestraße 2
97959 Assamstadt
Phone +49 62 94 42 24-0
Fax +49 62 94 42 24-100
sales@ecom-ex.com

¹ also covering Austria

ecom Benelux ²

ecom instruments BV
Watertoren 45c
3247 CL Dirksland, Netherlands
Phone +31 1 87 60 59 16
Fax +31 1 87 60 33 47
info.nl@ecom-ex.com

² also covering Belgium and Luxembourg

France ³

ecom Nied sarl
4 Rue Ettore Bugatti
67201 Eckbolsheim
Phone +33 3 88 76 46 84
Fax +33 3 88 76 02 85
info.fr@ecom-ex.com

³ also covering Algeria, Egypt, Morocco, Tunisia and Libya

Italy

ecom instruments srl
Via Gandhi, 15 Galleria
20017 Rho (MI)
Phone +39 02 93 90 92 16
Fax +39 02 93 90 62 97
info.it@ecom-ex.com

Switzerland

ecom instruments GmbH
Merkurstraße 2
6210 Sursee
Phone +41 4 19 21 60 00
Fax +41 4 19 22 00 08
info.ch@ecom-ex.com

United Kingdom

ecom instruments ltd
A310, The Wilton Centre,
Redcar, TS10 4RF,
United Kingdom
Phone +44 1642 46 54 00
Fax +44 1642 46 54 02
info.uk@ecom-ex.com

Nordics

ecom instruments GmbH
Postbox 304
2970 Hørsholm
Denmark
Phone +45 28 252 575
info.nordics@ecom-ex.com

Middle East

ecom instruments fze
P.O. Box 8918
Saif-Zone, Sharjah, UAE
Phone +971 6 5 57 34 30
Fax +971 6 5 57 34 31
info.uae@ecom-ex.com

Americas

USA Headquarters

ecom instruments Inc.
1779 Westborough Drive, Suite 102
Katy, Texas 77449
Phone +1 281 496 59 30
Fax +1 281 496 23 21
info.us@ecom-ex.com

Asia

South East Asia

ecom instruments (SEA) Pte Ltd.
12 Arumugam Road
#05-11 Lion Building B
Singapore 409958
Phone +65 61 00 33 29
Fax +65 63 99 33 29
info.sg@ecom-ex.com

